



MODELS		GS™-2046	
MEASUREMENTS		US	Metric
Working height maximum*		26 ft	8.10 m
A	Platform height maximum	20 ft	6.10 m
B	Platform length - outside	7 ft 5 in	2.26 m
	extended	10 ft 5 in	3.18 m
Slide-out platform extension deck		3 ft	.91 m
C	Platform width - outside	3 ft 9.3 in	1.15 m
Guardrail height		—	—
Toeboard height		6 in	.15 m
D	Height - stowed: folding guardrails	7 ft	2.13 m
	rails folded	5 ft 1 in	1.55 m
E	Length - stowed	7 ft 11 in	2.41 m
	extended	10 ft 10.5 in	3.31 m
F	Width	3 ft 10 in	1.17 m
G	Wheelbase	6 ft 1 in	1.85 m
H	Ground clearance - center	4 in	.10 m
I	- with pothole guards deployed	.75 in	.019 m

PRODUCTIVITY		
Lift capacity	1,200 lbs	544 kg
Lift capacity - extension deck	250 lbs	113 kg
Drive speed - stowed	2.2 mph	3.5 km/h
Drive speed - raised	0.5 mph	0.8 km/h
Gradeability - stowed**	30%	
Turning radius - inside	zero	zero
Turning radius - outside	7 ft 6 in	2.29 m
Raise / lower speed	30 / 33 sec	30 / 33 sec
Controls	proportional	
Drive	dual front wheel	
Multiple disc brakes	dual rear wheel	
Tires - solid non-marking	15 x 5 x 11 in	38 x 13 x 28 cm

POWER		
Power source	24 V DC (four 6 V 225 Ah batteries)	
Hydraulic system capacity	3.75 gal	14.2 L

WEIGHT***		
ANSI/CSA	3,977 lbs	1,804 kg
CE/AUS	4,351 lbs	1,974 kg